

GREEN TICKGT-1Guitar pedalSCREAMER



User manual

YERASOV.

PRECAUTIONS

•Avoid storing or operating the unit in humid conditions (not above 80%).

• After storage or transportation at a low temperature before turning on unit shall be stored at room temperature for at least 2 hours.


• Protect the device from falls, bumps, to get into foreign objects, liquids, dirt and rain.

GENERAL INFORMATION

GT-1 is an overdrive effect, made on the basis of the famous Ibanez Tube Screamer. With its help you can as a "warm up" your tube amp, and use it as an independent effect, which retains all the characteristics of natural warm overdrive. When used pedal as a booster, the sustain increases, almost without changing the character of the sound of your amp.

The pedal is collected on the most modern components: lownoise chip, precision resistors, electrolytic capacitors with low leakage currents. In the audio path only used film capacitors WIMA. In the pedal is applied 3DPDT foot switch from ALPHA for the TRUE BYPASS.

PANEL DESCRIPTION



- 1 VOLUME volume control knob
- 2 TONE tone control knob
- 3 DRIVE distortion control knob
- 4 on LED effect
- 5 Jack for DC adapter
- 6 FAT lift low-frequency switch
- 7 Input Jack
- 8 on / off button effect
- 9 output Jack

Polarity of DC 9V adapter



USE OF PRODUCT

Power supply of pedals GT-1 from the battery type 6F-22, which is installed under the bottom cover of the pedal, or from an external source of stabilized voltage 9V.

Turn on the power from the battery, when connecting the Jack (mono only) to the input Jack, so to prolong the battery life, do not leave Jack in the input connector.


Connect the DC adapter Jack (5) or the battery.

Connect the pedal as shown.

Turn on the amplifier.

Rotate the knobs adjust the sound you need.

When you use the pedal as a "warmer" recommend the use of minimum **DRIVE** knob and maximum of the regulator **VOLUME**.



GT-1

REPLACEMENT BATTERY

- Use only the adapter AD9-100 or AD9-500 by YERASOV.
- To prolong battery life, do not leave Jack in the input connector.
- To replace the battery, remove the cover by unscrewing the 4 screws. Replace the battery cover and set in place.

SPECIFICATIONS

Input impedance, kOhm	510
Recommended Load Impedance, kOhm	
Power Supply, V	9
Current Draw, mA	
Dimensions, mm:	126 54 94
Weight, kg	0,35

PACKAGE CONTENTS

Guita	r pedal	GT-1,	pcs1
User	Manual,	pcs	1

YERASOV.

YERASOV MUSIC CORPORATION

www.yerasov.ru e-mail: sale@yerasov.ru